

Die Part#	Die Description	Punched Edge Centerline	Edge Margin	Spacing	A5	1/2 LTR	LTR	A4
<b>T0047</b>	4:1 Coil Round							
47 Holes, Suggested for: A4 and A5		<b>Spacing:</b> 0.2475"(6.29mm) <b>Holes:</b> 0.188"(4.78mm) <b>Margin:</b> 0.188"(4.78mm)						
<b>T0048</b>	4:1 Coil Round							
48 Holes, Suggested for: LTR and 1/2 LTR		<b>Spacing:</b> 0.2475"(6.29mm) <b>Holes:</b> 0.188"(4.78mm) <b>Margin:</b> 0.188"(4.78mm)						
<b>T0247</b>	4:1 Coil Oval							
47 Holes, Suggested for: A4 and A5		<b>Spacing:</b> 0.2475"(6.29mm) <b>Holes:</b> 0.188"x0.156"(4.78x3.96mm) <b>Margin:</b> 0.188"(4.78mm)						
<b>T0248</b>	4:1 Coil Oval							
48 Holes, Suggested for: LTR and 1/2 LTR		<b>Spacing:</b> 0.2475"(6.29mm) <b>Holes:</b> 0.188"x0.156"(4.78x3.96mm) <b>Margin:</b> 0.188"(4.78mm)						
<b>T1136</b>	3:1 Wire Square							
36 Holes, Suggested for All Standard Sizes		<b>Spacing:</b> 0.3333"(8.47mm) <b>Holes:</b> 0.156"(3.96mm) <b>Margin:</b> 0.179"(4.55mm)						
<b>T2423</b>	2:1 Wire Square							
23 Holes, Suggested for: LTR and A4		<b>Spacing:</b> 0.500"(12.70mm) <b>Holes:</b> 0.250"(6.35mm) <b>Margin:</b> 0.250"(6.35mm)						
<b>T2424</b>	2:1 Wire Square							
24 Holes, Suggested for: 1/2 LTR and A5		<b>Spacing:</b> 0.500"(12.70mm) <b>Holes:</b> 0.250"(6.35mm) <b>Margin:</b> 0.250"(6.35mm)						
<b>T1736</b>	3:1 Wire Round							
36 Holes, Suggested for All Standard Sizes		<b>Spacing:</b> 0.3333"(8.47mm) <b>Holes:</b> 0.171"(4.34mm) <b>Margin:</b> 0.168"(4.27mm)						
<b>T2823</b>	2:1 Wire Round							
23 Holes, Suggested for: LTR and A4		<b>Spacing:</b> 0.500"(12.70mm) <b>Holes:</b> 0.250"(6.35mm) <b>Margin:</b> 0.250"(6.35mm)						
<b>T2824</b>	2:1 Wire Round							
24 Holes, Suggested for: 1/2 LTR and A5		<b>Spacing:</b> 0.500"(12.70mm) <b>Holes:</b> 0.250"(6.35mm) <b>Margin:</b> 0.250"(6.35mm)						
<b>T1135*</b>	3:1 Wire Square							
35 Holes, *Non-Standard Die		<b>Spacing:</b> 0.3333"(8.47mm) <b>Holes:</b> 0.156"(3.96mm) <b>Margin:</b> 0.179"(4.55mm)						
<b>T1735*</b>	3:1 Wire Round							
35 Holes, *Non-Standard Die		<b>Spacing:</b> 0.3333"(8.47mm) <b>Holes:</b> 0.171"(4.34mm) <b>Margin:</b> 0.168"(4.27mm)						
<b>T3321</b>	Comb							
21 Holes, Suggested for All Standard Sizes		<b>Spacing:</b> 0.5625"(14.29mm) <b>Holes:</b> 0.313"x0.125"(7.95x3.18mm) <b>Margin:</b> 0.200"(5.08mm)						
<b>T3320*</b>	Comb							
20 Holes, *Non-Standard Die		<b>Spacing:</b> 0.5625"(14.29mm) <b>Holes:</b> 0.313"x0.125"(7.95x3.18mm) <b>Margin:</b> 0.200"(5.08mm)						
<b>T4511</b>	Velo							
11 Holes, Suggested for LTR, 1/2 LTR and A5		<b>Spacing:</b> 1.00"(25.4mm) <b>Holes:</b> 0.125"(3.18mm) <b>Margin:</b> 0.125"(3.18mm)						
<b>T4512</b>	Velo							
12 Holes, Suggested for: A4		<b>Spacing:</b> 1.00"(25.4mm) <b>Holes:</b> 0.125"(3.18mm) <b>Margin:</b> 0.125"(3.18mm)						
<b>T9609</b>	Loose Leaf 3-5-7/2 Hole Medical							
9 Holes, Suggested for: LTR and 1/2 LTR		<b>Holes:</b> 0.313"(7.95mm) <b>Margin:</b> 0.313"(7.95mm)						
<b>T9604</b>	Loose Leaf ISO 838/888							
4 Holes, Suggested for: A4 and A5		<b>Holes:</b> 0.250"(6.35mm) <b>Margin:</b> 0.472"(12.0mm)						